

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number
WO 2004/058611 A1

(51) International Patent Classification⁷: **B65G 69/00**,
E01F 15/14

(21) International Application Number:
PCT/AU2003/001204

(22) International Filing Date:
15 September 2003 (15.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002953528 24 December 2002 (24.12.2002) AU

(71) Applicant and

(72) Inventor: **COWEY, Steven, John** [AU/AU]; 24 Ninth
Street, Wingfield, S.A. 5013 (AU).

(74) Agent: **MADDERNS**; 1st Floor, 64 Hindmarsh Square,
Adelaide, S.A. 5000 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: AN IMPROVED VEHICLE LOADING DOCK FENDER ASSEMBLY



(57) Abstract: The invention relates to a loading dock fender unit (12) which is adapted for attachment adjacent a dock leveller (11) of a loading dock (10), the fender unit comprising a mounting plate (13), an elongate track (19) fixed to and projecting from the front face of the mounting plate (13) centrally thereof, a solid rubber or rubber like fender (15) guided for vertical sliding movement along the track (19), and a spring loaded fender restraining mechanism (16) which supports the fender in a normal at rest position and is arranged to resist movement of the fender (15) when displaced downwards from the normal at rest position by an externally applied force. In use, when a vehicle trailer is backed up against the dock with its rear end making contact with the fender (15), any up or down movement of the trailer rear end will cause simultaneous up or down movement of the fender (15). Desirably, the fender (15) can slide upwards unrestrained by the spring loaded restraining mechanism from its normal at rest position, and return to such position under its own weight (with the external lifting force having been removed).

WO 2004/058611 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.